



Fuse-link, high speed, 1800 A, AC 600 V, size 3, 76 x 92 x 135 mm, aR, IEC, UL, single indicator

Catalog No. 170M6670

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1800
Rated voltage			AC 600 V
Construction size			size 3
Size			76 x 92 x 135 mm
Utilization category			aR
Status indicator			single indicator
Description			US style indicator style K for microswitch
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with centre-bolted tags
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	1800
Rated voltage		V	600
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720023_170M.pdf
-------------------------	---