

## Three Phase Bridge Rectifier, 25 A, 35 A


**D-63**
**FEATURES**

- Universal, 3 way terminals: push-on, wrap around or solder
- High thermal conductivity package, electrically insulated case
- Center hole fixing
- Excellent power/volume ratio
- UL E300359 approved
- Nickel plated terminals solderable using lead (Pb)-free solder; solder alloy Sn/Ag/Cu (SAC305); solder temperature 260 °C to 275 °C
- Designed and qualified for industrial and consumer level
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

| PRIMARY CHARACTERISTICS |                    |
|-------------------------|--------------------|
| $I_o$                   | 25 A, 35 A         |
| $V_{RRM}$               | 50 V to 1600 V     |
| Package                 | D-63               |
| Circuit configuration   | Three phase bridge |

**DESCRIPTION**

A range of extremely compact, encapsulated three phase bridge rectifiers offering efficient and reliable operation. They are intended for use in general purpose and instrumentation applications.

| MAJOR RATINGS AND CHARACTERISTICS |                 |                  |                  |                  |
|-----------------------------------|-----------------|------------------|------------------|------------------|
| SYMBOL                            | CHARACTERISTICS | VALUES<br>26MT.. | VALUES<br>36MT.. | UNITS            |
| $I_o$                             |                 | 25               | 35               | A                |
|                                   | $T_C$           | 70               | 60               | °C               |
| $I_{FSM}$                         | 50 Hz           | 360              | 475              | A                |
|                                   | 60 Hz           | 375              | 500              |                  |
| $i^2t$                            | 50 Hz           | 635              | 1130             | A <sup>2</sup> s |
|                                   | 60 Hz           | 580              | 1030             |                  |
| $V_{RRM}$                         |                 | 50 to 1600       |                  | V                |
| $T_J$                             |                 | -55 to +150      |                  | °C               |

**ELECTRICAL SPECIFICATIONS**

| VOLTAGE RATINGS        |              |  |  |  |
|------------------------|--------------|--|--|--|
| TYPE NUMBER            | VOLTAGE CODE | $V_{RRM}$ , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE<br>V | $I_{RRM}$ MAXIMUM AT $T_J$ MAXIMUM<br>mA |
| VS-26MT..<br>VS-36MT.. | 05           | 50   | 75   | 2  |
|                        | 10           | 100  | 150  |  |
|                        | 20           | 200  | 275  |  |
|                        | 40           | 400  | 500  |  |
|                        | 60           | 600  | 725  |  |
|                        | 80           | 800  | 900  |  |
|                        | 100          | 1000   | 1100   |  |
|                        | 120          | 1200   | 1300   |  |
|                        | 140          | 1400   | 1500   |  |
|                        | 160          | 1600   | 1700   |  |

| FORWARD CONDUCTION                                     |               |  |                           |               |               |                   |
|--|---------------|--|---------------------------|---------------|---------------|-------------------|
| PARAMETER  | SYMBOL        | TEST CONDITIONS  |                           | VALUES 26MT.. | VALUES 36MT.. | UNITS             |
| Maximum DC output current at $T_C$                     | $I_O$         | 120° rect. conduction angle  |                           | 25            | 35            | A                 |
|  |               |  |                           | 70            | 60            | °C                |
| Maximum peak, one-cycle non-repetitive forward current | $I_{FSM}$     | t = 10 ms  | No voltage reapplied      | 360           | 475           | A                 |
|  |               | t = 8.3 ms   |                           | 375           | 500           |                   |
|  |               | t = 10 ms  | 100 % $V_{RRM}$ reapplied | 300           | 400           |                   |
|  |               | t = 8.3 ms   |                           | 314           | 420           |                   |
| Maximum $I^2t$ for fusing                              | $I^2t$        | t = 10 ms  | No voltage reapplied      | 635           | 1130          | A <sup>2</sup> s  |
|  |               | t = 8.3 ms   |                           | 580           | 1030          |                   |
|  |               | t = 10 ms  | 100 % $V_{RRM}$ reapplied | 450           | 800           |                   |
|  |               | t = 8.3 ms   |                           | 410           | 730           |                   |
| Maximum $I^2\sqrt{t}$ for fusing                       | $I^2\sqrt{t}$ | $I^2t$ for time $t_x = I^2\sqrt{t} \times \sqrt{t_x}$ ; $0.1 \leq t_x \leq 10$ ms, $V_{RRM} = 0$ V |                           | 6360          | 11 300        | A <sup>2</sup> √s |
| Low level of threshold voltage                         | $V_{F(TO)1}$  | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , $T_J$ maximum                  |                           | 0.88          | 0.86          | V                 |
| High level of threshold voltage                        | $V_{F(TO)2}$  | $(I > \pi \times I_{F(AV)})$ , $T_J$ maximum   |                           | 1.13          | 1.03          |                   |
| Low level forward slope resistance                     | $r_{t1}$      | $(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$ , $T_J$ maximum                  |                           | 7.9           | 6.3           | mΩ                |
| High level forward slope resistance                    | $r_{t2}$      | $(I > \pi \times I_{F(AV)})$ , $T_J$ maximum   |                           | 5.2           | 5.0           |                   |
| Maximum forward voltage drop                           | $V_{FM}$      | $T_J = 25$ °C, $I_{FM} = 40$ A <sub>pk</sub> - per single junction                                 |                           | 1.26          | 1.19          | V                 |
| Maximum DC reverse current                             | $I_{RRM}$     | $T_J = 25$ °C, per junction at rated $V_{RRM}$   |                           | 100           |               | μA                |
| RMS isolation voltage                                  | $V_{INS}$     | $T_J = 25$ °C, all terminal shorted; f = 50 Hz, t = 1 s  |                           | 2700          |               | V                 |

| THERMAL - MECHANICAL SPECIFICATIONS            |                |   |             |             |       |
|--|----------------|---|-------------|-------------|-------|
| PARAMETER                                      | SYMBOL         | TEST CONDITIONS   | VALUES 26MT | VALUES 36MT | UNITS |
| Maximum junction and storage temperature range | $T_J, T_{Stg}$ |   | -55 to +150 |             | °C    |
| Maximum thermal resistance, junction to case   | $R_{thJC}$     | DC operation per bridge (based on total power loss of bridge) | 1.42        | 1.35        | K/W   |
| Maximum thermal resistance, case to heatsink   | $R_{thCS}$     | Mounting surface, smooth, flat and greased                    | 0.2         | 0.2         |       |
| Approximate weight                             |                |   | 20          |             | g     |
| Mounting torque ± 10 %                         |                | Bridge to heatsink with screw M4                              | 2.0         |             | Nm    |




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Forward Voltage Drop Characteristics





Fig. 3 - Total Power Loss Characteristics




Fig. 4 - Maximum Non-Repetitive Surge Current




Fig. 6 - Current Ratings Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics





Fig. 8 - Total Power Loss Characteristics





Fig. 9 - Maximum Non-Repetitive Surge Current

Fig. 10 - Maximum Non-Repetitive Surge Current




Fig. 11 - Thermal Impedance  $Z_{thJC}$  Characteristics





Fig. 12 - Thermal Impedance  $Z_{thJC}$  Characteristics

### ORDERING INFORMATION TABLE

|             |            |                                 |  |            |
|-------------|------------|---------------------------------|--|------------|
| Device code | <b>VS-</b> | <b>36</b>                       | <b>MT</b>                                  | <b>160</b> |
|             | ①          | ②                               | ③  | ④          |
|             | <b>1</b>   | - Vishay Semiconductors product |  |            |
|             | <b>2</b>   | - Current rating code           | 26 = 25 A (average)<br>36 = 35 A (average) |            |
|             | <b>3</b>   | - Basic part number             |  |            |
|             | <b>4</b>   | - Voltage code x 10 = $V_{RRM}$ |  |            |

### CIRCUIT CONFIGURATION




| LINKS TO RELATED DOCUMENTS |  |
|----------------------------|--|
| Dimensions                 | <a href="http://www.vishay.com/doc?95251">www.vishay.com/doc?95251</a> |



## D-63

**DIMENSIONS** in millimeters (inches)



Not to scale



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.